





Skirting board duct 80 in U23X

For distribution of power and data services and mounting of outlets through skirting boards in housing and buildings

- Allows you to lay out all services in housing and public buildings by taking the place of a conventional skirting board.
- Compact and plain trunking, with adjusted sizes, to perfectly merge into the surroundings.

Raw material







Safety

Electrical



- Insulating material
- No earthing required

Mechanical



• IK07

Protection degree



• IP4X, mounted on the wall

In front of fire



- Glow-wire test at 960 °C
- Non-flame propagator
- Reaction to fire, Class M1 acc./ UNE 23727 and NFP 92507

Quality marks







Approvals



TP FZ 123-FZ



Bureau Veritas

Conformity declaration



* BS EN 50085-2-1 is the UK implementation of EN 50085-2-1

Skirting board duct 80


Length: 2 m

Aluminium colour RAL 9006

White RAL 9010

See updated information of each part number on www.unex.net





Skirting board duct 80: a smart alternative to conventional skirting boards

The skirting board duct optimises the space dedicated to conventional decorative skirting boards by accommodating cables and feeding switches and sockets. It doesn't involve additional constructive elements.
















4 compartments for all services

The Skirting board duct 80 allows you a simultaneous lay out of all necessary wiring.



The system permits compliance with functional and safety requirements defined by the applicable regulations.





Integration in the environment

Its neutral colour (able to be painted like the wall or the floor) and its smoothed design, confer the appearance of a standard skirting board.



Free choice and composition of switches and sockets

Adapters for the most common switches and sockets

Switches and sockets are mounted outside the trunking by means of matching adapters.





Simon* 73 Loft Simon* 73 Loft





Universal CEE-7

Universal CEE-7






Mosaic* Simon* 27



Oteo*



Neat finishing



Complete system of fittings providing electrical safety (IP4X degree) and an attractive finish. **Available in white RAL 9010 and aluminium colour RAL 9006.**



External angle



Internal angle



Coupler




End cover



Mini trunking branching

Easy mounting

Skirting board duct and fittings






No power cables are to be installed in the lower compartment, thus ensuring safety distance from the floor (1,5 cm).

Protection of the junction between wall and floor



Switches and sockets



Skirting board duct in U23X white


	Skirting board duct 80	Skirting board duct sizes (mm)	16x100
White RAL 9010 (Part no. 80xxx-2) ☐			16 2 3 100
Skirting board duct 2 m			80034-2
ı	Fittings in U24X		
2		External angle	80284-2
3		Internal angle	80334-2
4	Ĵ	End cover	80384-2
5	(1 to 1 t	Coupler	80534-2
6 Branch to mini trunking		Branch to mini trunking	80434-2
ı	Fixing elements in U	33X	
7		Trunking plug Note: Use bit ∅ 4 mm.	25104
-	Adaptation of switch	es and sockets in U24X	
8		Adapter for 1 outlet Simon* 73 Loft	80882-2
9		Adapter for 1 universal (CEE) outlet	80700-2
10		Adapter for 1 outlet Simon* 27	80704-2
11		Adapter for 1 outlet Mosaic*	80702-2
12		Adapter for 1 outlet Oteo*	80880-2



Skirting board duct in U23X colour aluminium


	10.100		
,	Skirting board duct 80	Skirting board duct sizes (mm)	16x100
Aluminium colour RAL 9006 (Part no. 80xxx-03)			16
1		Skirting board duct 2 m	80034-03
	Fittings in U24X		
2	A A	External angle	80284-03
3	T II	Internal angle	80334-03
4	Î	End cover	80384-03
5	Coupler		80534-03
6		Branch to mini trunking	80434-03
	Fixing elements in U	63X	
7	7 Trunking plug Note: Use bit ∅ 4 mm.		25104
	Adaptation of switch	es and sockets in U24X	
8		Adapter for 1 outlet Simon* 73 Loft	80882-03
9		Adapter for 1 universal (CEE) outlet	80700-03
12		Adapter for 1 outlet Oteo*	80880-03

Sizes (mm)






Material: U63X



Part no. Colours		Mini trun applicat	Pack	
White	Aluminium			pc.
80434-2	80434-03	78010-2	78021-2	6
		78022-2	78023-2	
		78031-2	78033-2	
		78073-2	78083-2	
		78085-2	78031-04	
		78010-2A		
		78021-2A		
		78022-2A		
		78031-2A		
			Materia	ıl: U24X

Note: 1 screw included.




Part no.	Sizes mm A	Diameter plug mm	Pack pc.
25104	21	4	1.000

Colour: Black
Note: Use drill bit Ø 4 mm.


▲ Indoor use.

8. Adapter 1 outlet Simon* 73 Loft



Part no.		Pack
Colours		
White	Aluminium	pc.
80882-2	80882-03	12
		Material: U24X


9. Adapter 1 universal (CEE) outlet




65

Part no.	urs	Pack
White	Aluminium	рс.
80700-2	80700-03	12
		Material: U24X

10. Adapter 1 outlet Simon* 27



Note: 2 screws are included.	
Part no.	Pack
	pc.
80704-2	12
Colour: White RAL 9010	Material: U24X



Useful cross-sections (mm²)

Recommended capacity with conductors H07V-K

Sizes (mm) Part numbers			16x100			
			80034-2 80034-03			
		C ₁ 331 C ₂ 302 C ₃ 228 C ₄ 86				
		Compartments				
	Types of cables	Ø mm	C1	C2	C3	C4*
Power	H07V-K 1,5 mm ²	3,5	14	13	10	-
	H07V-K 2,5 mm ²	4,2	9	8	6	-
	H07V-K 4 mm ²	4,8	7	7	5	-
	H07V-K 6 mm ²	6,3	4	4	3	-
TV	Coaxial 75 Ohm	7,0	4	4	3	0
Telephone	1 pair EV 0,51 mm	3,7	13	12	9	3
	2 pairs EV 0,51 mm	4,0	11	10	8	3

^{*} To comply with regulations, no power cables are to be installed in the lower compartment, thus ensuring safety distance from the floor (1,5 mm).

PYRIGHT: All trademarks, brands or distinctive signs, of any kind, that might appear in the present website are the property of Un	nex
ellaje eléctrico, S.L. or of third parties. The use or access to the present website and/or to its services should not be interpreted, und ircumstances, as conferring any rights to the User on the mentioned trademarks, brands or distinctive signs. The removes, all Contents are the property of Unex aparellaje eléctrico, S.L. or of third parties. As stated in the mentioned Legal Notice, no	der
e operation rights existing or that might exist about the mentioned Contents should be understood as transferable to the User, beyo e strictly necessary for the correct use of the Portal and the Services.	